

WAAS
CH **86902**
W24A

APP CRS
241°

Rwy Idg
TDZE **16**
Apt Elev **18**

RNAV (GPS) RWY 24

BOWERMAN (HQM)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 43°C (109°F). When local altimeter setting not received, procedure NA. Circling NA northwest of Rwy 6-24. DME/DME RNP- 0.3 NA. For inoperative MALSR, increase LPV Cat C visibility to ¾ mile and LNAV Cat C visibility to 2½ miles.

MALSR

MISSED APPROACH:
Climb to 2600 direct ZUNAD and hold.

ASOS 135.775	SEATTLE CENTER 128.3 269.0	UNICOM 122.7 (CTAF) 0
------------------------	--------------------------------------	---------------------------------

ELEV 18	TDZE 16
----------------	----------------

2600 ZUNAD

* LNAV Only.

FODUL 2.3 NM to RW24

NEYDI 2100

LAMMB

2900

241° to RW24

241°

061°

2900 NoPT (170.4)

2900 NoPT (9.6)

GP 3.50° TCH 55

CATEGORY	A	B	C	D
LPV DA	226-½	210 (300-½)	286-½ 270 (300-½)	NA
LNAV/VNAV DA	676-1½		660 (700-1½)	NA
LNAV MDA	800-½ 784 (800-½)	800-¾ 784 (800-¾)	800-1¾ 784 (800-1¾)	NA
CIRCLING	800-1 782 (800-1)	800-1¼ 782 (800-1¼)	800-2¼ 782 (800-2¼)	NA

HOQUIAM, WASHINGTON

Amdt 2E 07OCT21

46°58'N-123°56'W

BOWERMAN (HQM)

RNAV (GPS) RWY 24